

Rittal – The System.

Faster – better – everywhere.



AX 2262.130

AX wall-mounted housing, 3-part

State: 5/30/2026 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AX 2262.130 - AX wall-mounted housing, 3-part

The delivery concept of the three-part AX wall-mounted enclosure reduces complexity and increases flexibility. Thanks to the AX/VX modular system, the enclosures are suitable for various applications. The three-part structure ensures easy access.



Features

| | |
|-----------------|--|
| Model No. | AX 2262.130 |
| Version | Wall-mounted housing IT |
| Material | Wall and hinged part: Carbon steel, 1.5 mm Viewing window: Single-pane safety glass, 3 mm |
| Surface finish | Powder-coated |
| Color | Wall and hinged part: RAL 7035 Viewing door: RAL 7035/7015 (slate gray) |
| Supply includes | Wall section: Flange (gland) plate, solid, top and bottom Hinged part with 25 mm pitch pattern in the front and rear frame, two 19" profile angles at the front, fixed in place Designer viewing door Center part lock: 3 mm double bit Lock design – glazed door: Security lock 3524 E Comfort handle for lock inserts and 2-point locking |
| Height units | 21 U |

Features

| | |
|---------------------------------------|--|
| Dimensions | Width: 600 mm Height: 1,012 mm Depth: 373 mm Width: 23.6 " Height: 39.8 " Depth: 14.7 " |
| Installation depth | 320 mm 12.6 " |
| Clearances | Clearance width: 502 mm Clearance height: 951 mm Clearance width: 19.8 " Clearance height: 37.4 " |
| Depth hinged part | 216 mm 8.5 " |
| Depth of wall section | 135 mm 5.31 " |
| No. of locks | 1 |
| Load capacity of hinged part (static) | 750 N |
| Load capacity wall section (static) | 250 N |
| Base material | Carbon steel |
| Lock | Lock version: Comfort handle and 2-point locking Lock Insert: Security lock insert no. 3524 E |
| Protection category IP to EN 60529 | IP 54 in conjunction with solid gland plate top and bottom |
| Packaging unit | 1 pc(s). |
| Net weight | 43 kg |
| Gross weight | 44 kg |
| Information regarding the PCF class | Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared |
| Customs tariff number | 94032080 |
| ETIM 9 | EC002500 |

Features

| | |
|---------------------|---|
| ETIM 8 | EC002500 |
| ECLASS 8.0 | 27180101 |
| Product description | AX wall-mounted housing AX, 3-part, WHD: 600x1,012x373 mm, 21 HE, wall section: closed flange plate top and bottom, with comfort handle |

Approvals

| | |
|--------------|---------------------------|
| Approvals | UL + C-UL (listed) |
| Explanations | Declaration of conformity |