Rittal – The System.

Faster – better – everywhere.





AX 2262.150 AX wall-mounted housing, 3-part

State: 9/15/2025 (Source: rittal.com/us-en)



AX 2262.150 - AX wall-mounted housing, 3-part

The delivery concept of the three-part AX wall-mounted enclosure reduces complexity and increases flexibility. Thanks to the AX/VX modular system, the enclosures are suitable for various applications. The three-part structure ensures easy access.



Features

Height units	21 U
	Comfort handle for lock inserts and 2-point locking
	Lock design – glazed door: Security lock 3524 E
	Center part lock: 3 mm double bit
	Designer viewing door
	two 19" profile angles at the front, fixed in place
	Hinged part with 25 mm pitch pattern in the front and rear frame
Supply includes	Wall section: Flange (gland) plate, solid, top and bottom
	Viewing door: RAL 7035/7015 (slate gray)
Color	Wall and hinged part: RAL 7035
Surface finish	Powder-coated
	Viewing window: Single-pane safety glass, 3 mm
Material	Wall and hinged part: Carbon steel, 1.5 mm
Version	Wall-mounted housing IT
Model No.	AX 2262.150

Features

Dimensions	Width: 600 mm
	Height: 1,012 mm
	Depth: 573 mm
	Width: 23.6 "
	Height: 39.8 ″
	Depth: 22.6 "
No. of locks	1
Load capacity of hinged part (static)	750 N
Load capacity of wall section (static)	250 N
Base material	Carbon steel
Lock	Lock version: 2-point locking
	Lock Insert: Comfort handle and 2-point locking
Protection category IP to EN 60 529	IP 54 in conjunction with solid gland plate top and bottom
Packaging unit	1 pc(s).
Net weight	53
Gross weight	55
PCF/VE (cradle-to-gate)	208.6 kg CO2 eq (Cat B)
Information regarding the PCF class	Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared
Customs tariff number	94032080
EAN	4028177982963
ETIM 9	EC002500
ETIM 8	EC002500
ECLASS 8.0	27180101

Approvals



Explanations

Declaration of conformity