Rittal – The System.

Faster – better – everywhere.



AX 2394.100

Base configuration rail

State: 11/16/2026 (Source: www.rittal.com/us-en)

AX 2394.100 - Base configuration rail for AX

Rail for flexible interior configuration of AX compact enclosures in combination with the new AX rail for interior installation. For mounting e.g. VX system chassis with mounting flange 23 x 64 mm, LED system lights, VX cable clamp rails and support rails.





Features

Model No.	AX 2394.100
Product description	For mounting in the enclosure depth, on the existing threaded bolts, no machining required. System punchings on 2 sides. Provides additional mounting options.
Material	Carbon steel
Surface finish	Zinc-plated
Supply includes	Assembly components
Length	99 mm 3.9 ″
Installation options	For installation in AX carbon steel, only in conjunction with rails interior installation AX
Suitable for	Enclosure type: AX
Packaging unit	4 pc(s).
Net weight	0.4 kg
Gross weight	0.451 kg
PCF/VE (cradle-to-gate)	1.6 kg CO2 eq (Cat B)
Information regarding the PCF class	Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared
Customs tariff number	73269098

© Rittal 2026

Features

ETIM 9	EC002620
ETIM 8	EC002620
ECLASS 8.0	27189234
Product description	AX base configuration rail