

Faster – better – everywhere.





TP 2683.600 One-piece consoles

CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

State: 8/8/2025 (Source: rittal.com/us-en)

POWER DISTRIBUTION



FRIEDHELM LOH GROUP

ENCLOSURES

TP 2683.600 - One-piece consoles Stainless steel

Console made from stainless steel 1.4301, (AISI 304), ready-to-use unit with high protection category IP 55 in four different widths. Easy handling thanks to self-locking lid stay. Interchangeable lock insert. Easy cable entry thanks to split base plates.



Features

Model No.	TP 2683.600
	TF 2083.000
Material	Housing: Stainless steel 1.4301 (AISI 304), 1.5 mm
	Door or double door and console lid: Stainless steel 1.4301 (AISI
	304), 2.0 mm
	Mounting panel: Carbon steel, 3.0 mm
Surface finish	Housing, door, console lid and base plates: Brushed, grain 400
	Mounting panel: Zinc-plated
Supply includes	Housing, solid back and sides
	Door or double door at front, with locking rod
	Console lid with lid stay and cam lock latched in the enclosure
	Locks with double-bit insert
	Base plates, divided
	Mounting panel
Dimensions	Width: 600 mm
	Height: 960 mm
	Width: 23.6 "
	Height: 37.8 ″
Dimensions of mounting plate (W	530 mm x 780 mm
x H)	20.9 ″ x 30.7 ″

Features

Top depth	480 mm
	18.9 ″
Bottom depth	400 mm
	15.7 ″
Number of doors	1
Protection category IP to IEC 60 529	IP 55
Protection category NEMA	NEMA 12
Base material	Stainless steel 1.4301 (AISI 304)
Dimensions	Width: 600 mm
	Height: 960 mm
	Top depth: 480 mm
	Bottom depth: 400 mm
	Width: 23.6 ″
	Height: 37.8 [″]
	Top depth: 18.9 [~]
	Bottom depth: 15.7 "
Packaging unit	1 pc(s).
Net weight	47.85
Gross weight	52
Customs tariff number	94032080
EAN	4028177031319
ETIM 9	EC000784
ETIM 8	EC000784
ECLASS 8.0	27180504

Approvals

Approvals	TÜV
	UL + C-UL (listed)



Explanations

Declaration of conformity Declaration of conformity UK