

Rittal – The System.

Faster – better – everywhere.



FT 2740.000 Operating panel

State: 8/29/2025 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



FT 2740.000 - Operating panel for AE/WM

Mounted on AE enclosures instead of door and on surfaces. Frame structure with internal corner connectors, 3 mm aluminum plate secured from the inside and sealed against the frame.



Features

Model No.	FT 2740.000
Product description	Can be used as a door on AE enclosures or mounted on enclosures with sufficient surface area. Frame structure with internal corner connectors, 3 mm aluminum plate secured from the inside and sealed against the frame.
Material	Aluminum, natural anodized
Supply includes	Aluminum frame Display panel Hinges Brackets
Protection category IP to EN 60 529	IP 54
Note	During installation, the cam lock is required in place of the door
Suitable for	Enclosure type: AE Width: = 200 mm Height: = 300 mm Enclosure type: AE Width: = 7.87 " Height: = 11.8 "

Features

Dimensions	Width: 197 mm Height: 297 mm Depth: 34 mm Width: 7.76 " Height: 11.7 " Depth: 1.34 "
Dimensions of aluminium plate	Width: 143 mm Height: 243 mm Width: 5.63 " Height: 9.57 "
Area available for population	Width: 127 mm Height: 227 mm Width: 5 " Height: 8.94 "
Note on Model No.:	With AE, only for use on the rear panel
Packaging unit	1 pc(s).
Net weight	1.237
Gross weight	1.42
Customs tariff number	76169990
EAN	4028177031838
E-Number Sweden	E3404521
ETIM 9	EC000747
ETIM 8	EC000747
ECLASS 8.0	27182204