## Rittal – The System.

Faster – better – everywhere.





# SK 3105.390 Enclosure Heater

State: 12/3/2025 (Source: rittal.com/us-en)



## SK 3105.390 - Enclosure Heater with fan

Enclosure heaters to regulate relative humidity, prevent temperatures from dropping below the dew point and stop condensation forming inside the enclosure. This prevents consequential damage associated with corrosion or electrical short circuits. Version with fan. Continuous thermal output 235 – 800 W.







#### **Features**

Model No.	SK 3105.390
Product description	Enclosure heaters to regulate relative humidity, prevent temperatures from dropping below the dew point and stop condensation forming inside the enclosure. This prevents consequential damage associated with corrosion or electrical short circuits.
Material	Aluminum, anodized
Supply includes	PTC heater with fan Fasteners
Continuous thermal output	Continuous thermal output with fan
Integrated fan	Yes
Note	A thermostat is recommended for precise temperature control inside the enclosure In order to prevent condensation on assemblies, hygrostat is recommended to regulate heating In larger enclosures, even heat distribution is best achieved by installing several low-output heaters.

© Rittal 2025 2

## **Features**

Note on Model No.:	Operation at a temperature of -40 °C is possible. Upon request, you will receive a manufacturer's declaration.
Continuous thermal output at	400 W - 415 W
10 °C	1,365 BTU/h - 1,416 BTU/h
Rated operating voltage	230 V, 1~, 50 Hz/60 Hz
Dimensions	Width: 103 mm
	Height: 200 mm
	Depth: 103 mm
	Width: 4.06 "
	Height: 7.87 "
	Depth: 4.06 "
Pre-fuse	Miniature circuit-breaker/fuse: 6 A
Protection category IP to IEC 60 529	IP 20
Protection category	II (total insulation)
Operating temperature range	-33 °C65 °C
	-27 °F149 °F
Packaging unit	1 pc(s).
Net weight	1
Gross weight	1.192
Customs tariff number	85162999
EAN	4028177662872
E-Number Sweden	E3404405
ETIM 9	EC000737
ETIM 8	EC000737
ECLASS 8.0	27180710

# **Approvals**

© Rittal 2025 3

# Approvals

Approvals	CSA UR + C-UR (recognized)
Explanations	Declaration of conformity  Declaration of conformity UK

© Rittal 2025