Rittal - The System.

Faster – better – everywhere.





SK 3179.800 Wall-mounted cooling unit Blue e+ S

State: 11/28/2025 (Source: rittal.com/us-en)



SK 3179.800 - Wall-mounted cooling unit Blue e+ S 1023.64 - 3412.14 BTU/h

Blue e+ S cooling units with proven Blue e+ technology offer the world's highest energy efficiency. This is also linked with a reduction in the CO\(\text{M}\) footprint of machinery and equipment. In a new design and with many smart functions.



Features

Model No.	SK 3179.800	
Version	wall-mounted	
Benefits Helps make production climate-neutral thanks to average savings of 75% and reduction of CO2 footprint Universal compatibility due to multi-voltage capability specific approvals Intelligent and easy monitoring via IoT interface Convenient operation with the Rittal Scan & Service A		
Material	Carbon steel	
General color	RAL 7035	
Color	Housing: RAL 7035 Louvered grille: RAL 7012	
Supply includes	Assembly components Wired ready for connection (plug-in terminal strip) Integral electric condensate evaporation	
Options	For remote monitoring and networking of cooling units and chillers, use the Blue e+ Generation IoT Interface, item number 3124.300. Increase machine availability and process safety by remote monitoring of device data, condition, and system messages.	

© Rittal 2025 2

Features

Total cooling output to DIN EN	Cooling output L35 L35/50 Hz: 0.52 kW	
14511	Cooling output L35 L35/60 Hz: 0.52 kW	
	Cooling output L35 L50/50 Hz: 0.32 kW	
	Cooling output L35 L50/60 Hz: 0.32 kW	
	Cooling output L35 L35/50 Hz: 1,774 BTU/h	
	Cooling output L35 L35/60 Hz: 1,774 BTU/h	
	Cooling output L35 L50/50 Hz: 1,092 BTU/h	
	Cooling output L35 L50/60 Hz: 1,092 BTU/h	
Rated operating voltage	110 V - 240 V, 1~, 50 Hz/60 Hz	
Note	Please observe the assembly instructions.	
	When the software is downloaded, a contract is concluded between	
	the contractual partner and Rittal for the free use of the software in	
	accordance with these license conditions.	
	Only for semi-outdoor use (see instructions for description)	
Note on Model No.:	Tolerance: 110 V -10% (99 V) and 240 V +10% (264 V)	
Rated output	0.36 kW	
Air throughput (unimpeded air	External circuit: 366.6 m³/h	
flow)	Internal circuit: 366.6 m³/h	
	External circuit: 215.8 cfm	
	Internal circuit: 215.8 cfm	
Energy efficiency ratio (EER) 50/60	Refrigeration factor L35 L35 (EER) 50 Hz: 1.9	
Hz L35 L35	Refrigeration factor L35 L35 (EER) 60 Hz: 1.9	
Version	wall-mounted	
Dimensions	Width: 300 mm	
	Height: 570 mm	
	Depth: 199 mm	
	Width: 11.8 "	
	Height: 22.4 "	
	Depth: 7.83 "	
Required mounting cut-out	Width of opening: 280 mm	
	Cut-out height: 550 mm	
	Width of opening: 11 "	
	Cut-out height: 21.7 "	
Protection category IP to EN 60 529	Internal circuit IP 55	

© Rittal 2025 3

Features

Protection category NEMA	UL Type 12 UL Type 3R
Refrigerant/cooling medium	Refrigerant: R-513A Quantity: 0.16 kg Global Warming Potential (GWP): 631 CO2 equivalent (CO2e): 0.1 t Refrigerant: R-513A Quantity: 0.4 lb.
Temperature control	e+ controller (factory setting +35 °C)
Operating temperature range	-20 °C60 °C -4 °F140 °F
Storage temperature range	-40 °C70 °C -40 °F158 °F
Operating temperature range of refrigerant circuit (active)	3 °C60 °C
Operating temperature range of heat pipe	-20 °C45 °C
Setting range	20 °C50 °C 68 °F122 °F
Rated power Pel	Rated power L35 L35/50 Hz: 0.27 kW Rated power L35 L35/60 Hz: 0.27 kW Rated power L35 L50/50 Hz: 0.32 kW Rated power L35 L50/60 Hz: 0.32 kW
Permissible operating pressure (p. max.)	32 bar 464.1 PSI
Packaging unit	1 pc(s).
Net weight	12.841
Gross weight	13.84
Customs tariff number	84158200
EAN	4028177949966
ETIM 9	EC000855
ETIM 8	EC000855

© Rittal 2025

Features

ECLASS 8.0	27180704

Approvals

Approvals	30 - KC Korea	
	UL + C-UL (listed)	
	UL + C-UL - FTTA	
Explanations	Declaration of conformity	
	Declaration of conformity - F-gas regulation	

© Rittal 2025 5