

Faster – better – everywhere.





SK 3237.400 Blue e+ outlet filter

State: 9/2/2025 (Source: rittal.com/us-en)



POWER DISTRIBUTION CLIMATE CONTROL

TI INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

ENCLOSURES

SK 3237.400 - Blue e+ outlet filter EMC

The outlet filter is used in conjunction with the associated filter fan to dissipate lost heat out of the enclosures, to ventilate the enclosure and to protect temperature-sensitive components. This is done via the direct supply of ambient air that must be below the permissible temperature inside the enclosure.



Features

Model No.	SK 3237.400
Version	wall-mounted EMC
Benefits	Easy filter change thanks to a new opening mechanism on the louvre grille
	Faster assembly on the enclosure due to optimized snap hooks Tool-free mounting
Color	RAL 7035
Supply includes	Outlet Filters
	EMC Filter Mat
Mounting cut-out	Width of opening: 92 mm
	Cut-out height: 92 mm
	Width of opening: 3.62 "
	Cut-out height: 3.62 "
Suitable for Model No.	SK 3237.8xx

Features

Dimensions	Width: 116.5 mm
	Height: 116.5 mm
	Depth: 33.2 mm
	Width: 4.59 ″
	Height: 4.59 "
	Depth: 1.31 "
Protection category NEMA	Type 12 with fleece filter
	Type 3, 3R with fleece filter and hose-proof hood
Protection category IP to IEC 60	IP 54 with fleece filter
529	IP 56 with fleece filter and hose-proof hood
Packaging unit	1 pc(s).
Net weight	0.075
Gross weight	0.154
Customs tariff number	39269097
EAN	4028177998414
ETIM 9	EC002513
ETIM 8	EC002513
ECLASS 8.0	27180706

Approvals

Approvals

UL + C-UL - FTTA UR + C-UR (recognized)