Rittal – The System.

Faster – better – everywhere.





SK 3243.400 Blue e+ outlet filter

State: 11/4/2025 (Source: rittal.com/us-en)



SK 3243.400 - Blue e+ outlet filter EMC

The outlet filter is used in conjunction with the associated filter fan to dissipate lost heat out of the enclosures, to ventilate the enclosure and to protect temperature-sensitive components. This is done via the direct supply of ambient air that must be below the permissible temperature inside the enclosure.







Features

Model No.	SK 3243.400
Version	wall-mounted EMC
Benefits	Easy filter change thanks to a new opening mechanism on the louvre grille
	Faster assembly on the enclosure due to optimized snap hooks Tool-free mounting
Color	RAL 7035
Supply includes	Outlet Filters
	EMC Filter Mat
Mounting cut-out	Width of opening: 292 mm
	Cut-out height: 292 mm
	Width of opening: 11.5 "
	Cut-out height: 11.5 "
Suitable for Model No.	SK 3243.8xx/3244.8xx/3245.8xx

© Rittal 2025 2

Features

Dimensions	Width: 323 mm
	Height: 323 mm
	Depth: 44.7 mm
	Width: 12.7 "
	Height: 12.7 "
	Depth: 1.76 "
Protection category NEMA	Type 12 with fleece filter
	Type 3, 3R, 4, 4X with fleece filter and hose-proof hood
Protection category IP to IEC 60 529	IP 54 with fleece filter
	IP 56 with fleece filter and hose-proof hood
Packaging unit	1 pc(s).
Net weight	0.94
Gross weight	0.941
Customs tariff number	39269097
EAN	4028177998315
ETIM 9	EC002513
ETIM 8	EC002513
ECLASS 8.0	27180706

Approvals

Approvals	UL + C-UL - FTTA
	UR + C-UR (recognized)

© Rittal 2025 3