

Rittal – The System.

Faster – better – everywhere.



SK 3286.970

Air duct system

State: 1/16/2026 (Source: rittal.com/us-en)



FRIEDHELM LOH GROUP

SK 3286.970 - Air duct system for roof-mounted cooling units and roof-mounted air-water heat exchangers

Cold air can be routed directly to specific areas of the enclosure using the air duct system. This eliminates the risk of air short circuits due to self-ventilated installed devices. The shallow ducts can be cut to the desired length.

Features

| | |
|------------------------|--|
| Model No. | SK 3286.970 |
| Product description | Cold air can be routed directly to specific areas of the enclosure using the air duct system. This eliminates the risk of air short circuits due to self-ventilated installed devices. The dimensions of the shallow duct are W x H x D 229 x 1500 x 29 mm, and can be shortened to the required length. |
| Material | Flame-resistant plastic to DIN 4102/B1 |
| Color | RAL 7035 |
| Supply includes | Flat duct Compensating hose (length approx. 1 m) |
| Note | Do not direct cold air straight at active components. When using the ducting system, the performance of the cooling unit may be reduced, depending on the application in question. For devices 3359..../3382...., the air duct adapter 3286.840 is additionally required. |
| Suitable for Model No. | 3386.... 3387.... |
| Packaging unit | 1 pc(s). |
| Net weight | 2.9 |
| Gross weight | 3 |
| Customs tariff number | 39269097 |
| EAN | 4028177325456 |
| ETIM 9 | EC011444 |

Features

ETIM 8 EC011444

ECLASS 8.0 22410601

Approvals

Certificates EAC