
Rittal – The System.

Faster – better – everywhere.



SV 3515.000

PLS busbar connectors


State: 11/14/2026 (Source: www.rittal.com/us-en)

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

SV 3515.000 - PLS busbar connectors

For connecting/splicing the PLS busbar, no drilling required.



Features

Model No.	SV 3515.000
Product description	For connecting/splicing the PLS busbars. Drilling is not required.
Material	E-Cu
Surface finish	Nickel-plated
Rated current (max.)	1,368 A
Suitable for busbars	PLS 1600
Suitable for Model No.	9342.000 9342.004 9342.050
Connection type	Baying connection from enclosure to enclosure
Dimensions	Length: 150 mm Length: 5.91 ˝
Packaging unit	3 pc(s).
Net weight	3.81 kg
Gross weight	4.015 kg
Copper weight (kg per piece)	1.27
Customs tariff number	85369010
ETIM 9	EC000713

© Rittal 2026

Features

ETIM 8	EC000713
ECLASS 8.0	27400606
Product description	SV Busbar connector, PLS 1600, bayed connection

Approvals

Approvals	ABS DNV Lloyds Register UL + C-UL (listed)
Explanations	Declaration of conformity Declaration of conformity UK