


# Rittal – The System.

Faster – better – everywhere.



## SZ 4000.038

## Attachment with slope

State: 7/20/2025 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SZ 4000.038 - Attachment with slope for VX

For retrofitting individual or bayed VX25 stainless steel enclosures, with the largest possible opening at the joining point to the neighboring roof.



## Features

Model No.	SZ 4000.038
Technical specifications	Roof overhang in front: 8 mm
Material	Stainless steel 1.4301 (AISI 304)
Surface finish	Brushed, grain 400
Supply includes	Assembly components and seals
Dimensions	Height, front: 35 mm Height, front: 1.38 ~
Protection category IP to IEC 60529	IP 55
Protection category NEMA	NEMA 12
Note on Model No.:	Please quote the complete design code on all inquiries and orders. Delivery times on request.

# Features

Execution code	Roof pitch: 1 = 30° (EHEDG standard) or 2 = 45° Enclosure width: ... mm (max. 1200 mm) Enclosure depth: ... mm 1 = for VX single enclosure 2 = for aligned VX end enclosure on the left (each with a T-profile seal and connection accessories) 3 = for aligned VX end cabinet on the right (each with a T-profile seal and connection accessories) 4 = for aligned VX enclosure center (each with a T-profile seal and connection accessories) Example: 1 - 800 - 600 - 1 (attachment with slope with 30° roof pitch - width 800 mm - depth 600 mm - for VX single cabinet)
Packaging unit	1 pc(s).
Net weight	2
Gross weight	2.1
Customs tariff number	94039910
EAN	4028177937147