

Rittal – The System.

Faster – better – everywhere.



AS 4050.005 Smart Lifter

State: 4/18/2026 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AS 4050.005 - Smart Lifter

Lifting and transport device for enclosures and enclosure suites up to 4.80 m in length.



Features

Model No.	AS 4050.005
Product description	Lifting and transport device for enclosures and enclosure suites up to 4.80 m length.
Benefits	Supports simple mounting of base/plinths beneath enclosures Easy transportation of bayed enclosures in the workshop or at the installation site Flexible use for enclosures with different depths due to adjustable forks Ergonomic working (lifting and lowering) with a torque crank
Technical specifications	Dimensions of cart (W x H x D): 750 x 1100 x 400 mm
Function principle	Transport of bayed boxes up to a length of 4.80 m Transportable enclosure depths: 400, 500, 600, 800 mm Lifting of bay cabinets up to a height of 230 mm and a weight of 1,800 kg
Supply includes	2 transport carts
Load	1,800 kg 3,968.3 lb.
Packaging unit	1 pc(s).
Net weight	180 kg
Gross weight	195 kg
Customs tariff number	84279000

Features

ETIM 9	EC001203
ETIM 8	EC001203
ECLASS 8.0	21079190
Product description	Lifting and transport device for enclosures and enclosure suites. Supports easy mounting of bases under switchboards, as well as flexible transport of complete switchboards up to 1.8t. Adjustable forks allow VX control enclosures of depths 400, 500, 600 and 800 mm to be transported.

Approvals

Explanations	Declaration of conformity
--------------	---------------------------