

# Rittal – The System.

Faster – better – everywhere.



## AS 4051.220 Vibrofeeder pot WT

State: 4/21/2026 (Source: [rittal.com/us-en](http://rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# AS 4051.220 - Vibrofeeder pot WT

WT 16 vibrofeeder pot for feeding loose wire end ferrules with plastic collars for cross-sections of 0.5 mm<sup>2</sup> in the Wire terminal WT C fully automated wire cabling machine.



## Features

|                        |   |
|------------------------|---|
| Model No.              | AS 4051.220   |
| Benefits               | Process-safe feeding of wire end ferrules<br>Easy and quick replacement of consumables  |
| Supply includes        | Vibrofeeder pot WT 16   |
| Applications           | For loose wire end ferrules with cross-section 0.5 mm <sup>2</sup>  |
| Note                   | The oscillating conveyor pots and the separation of the ferrules are designed for the tolerance dimensions of the Rittal wire end ferrules according to DIN 46228-4:2019-02. If the wire end ferrules to be processed deviate from the tolerance dimensions defined therein, it may be necessary, on the one hand, to design/test new vibrofeeder pots and, on the other hand, to adjust the separation of the wire end ferrules. |
| Standards              | AEH DIN 46228   |
| Suitable for Model No. | 4051.205<br>4051.210  |
| Customs tariff number  | 84799070  |