Rittal – The System.

Faster – better – everywhere.



AS 4051.221
Vibrofeeder pot WT

State: 11/22/2026 (Source: www.rittal.com/us-en)

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

AS 4051.221 - Vibrofeeder pot WT

WT 20 vibrofeeder pot for feeding loose wire end ferrules with plastic collars for cross-sections of 0.75 and 1.0 mm² in the Wire terminal WT C fully automated wire cabling machine.



Features

Model No.	AS 4051.221
Benefits	Process-safe feeding of wire end ferrules Easy and quick replacement of consumables
Supply includes	Vibrofeeder pot WT 20
Applications	For loose wire end ferrules with cross-section 0.75 mm² and 1.0 mm²
Note	The oscillating conveyor pots and the separation of the ferrules are designed for the tolerance dimensions of the Rittal wire end ferrules according to DIN 46228-4:2019-02. If the wire end ferrules to be processed deviate from the tolerance dimensions defined therein, it may be necessary, on the one hand, to design/test new vibrofeeder pots and, on the other hand, to adjust the separation of the wire end ferrules.
Standards	AEH DIN 46228
Suitable for Model No.	4051.205 4051.210
Packaging unit	1 pc(s).
Net weight	0.4 kg
Gross weight	0.7 kg
Customs tariff number	84799070