

# Rittal – The System.

Faster – better – everywhere.



## AS 4051.223 Vibrofeeder pot WT

State: 5/22/2026 (Source: [rittal.com/us-en](http://rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# AS 4051.223 - Vibrofeeder pot WT

WT 43 vibrofeeder pot for feeding loose wire end ferrules with plastic collars for cross-sections of 4.0 and 6.0 mm<sup>2</sup> in the Wire terminal WT C fully automated wire cabling machine.



## Features

Model No.	AS 4051.223
Benefits	Process-safe feeding of wire end ferrules Easy and quick replacement of consumables
Supply includes	Vibrofeeder pot WT 43
Applications	For loose wire end ferrules with cross-section 4.0 mm <sup>2</sup> and 6.0 mm <sup>2</sup>
Note	The oscillating conveyor pots and the separation of the ferrules are designed for the tolerance dimensions of the Rittal wire end ferrules according to DIN 46228-4:2019-02. If the wire end ferrules to be processed deviate from the tolerance dimensions defined therein, it may be necessary, on the one hand, to design/test new vibrofeeder pots and, on the other hand, to adjust the separation of the wire end ferrules.
Standards	AEH DIN 46228
Suitable for Model No.	4051.205 4051.210
Customs tariff number	84799070