

# Rittal – The System.

Faster – better – everywhere.



## AS 4051.231 Wire rail WT

State: 7/11/2026 (Source: [rittal.com/us-en](http://rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE


SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# AS 4051.231 - Wire rail WT

The ready-cabled wires are fed to the WT 26 wire rail with a cross-section of 0.5 mm<sup>2</sup> by removal handling.



## Features

Model No.	AS 4051.231
Benefits	Project-related commissioning for downstream processes Project-related sorting of wires Optimal removal handling Rail system prepared for optimal workplace picking No wire sorting required Simplifies wiring process with step-by-step instructions in Eplan Smart Wiring Optimal in combination with the Wire Cart for perfect workstation commissioning
Supply includes	Wire rail WT 26
Note	The gap dimension indicates the maximum diameter of the wire insulation.
Suitable for Model No.	4051.205 4051.210 4051.024 4051.036
Applications	For single wires with cross-section 0.5 mm <sup>2</sup> (clearance 2.6 mm)
Packaging unit	1 pc(s).
Net weight	0.85 kg
Gross weight	1 kg
Customs tariff number	76169990

# Features

---

Product description

Wire rail 0.5 mm<sup>2</sup> for the 15-fold rail system in the WT