

Rittal – The System.

Faster – better – everywhere.



AS 4051.234 Wire rail WT

State: 4/25/2026 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AS 4051.234 - Wire rail WT

The ready-cabled wires are fed to the WT 35 wire rail with a cross-section of 1.5 mm² by removal handling.



Features

Model No.	AS 4051.234
Benefits	<ul style="list-style-type: none">Project-related commissioning for downstream processesProject-related sorting of wiresOptimal removal handlingRail system prepared for optimal workplace pickingNo wire sorting requiredSimplifies wiring process with step-by-step instructions in Eplan Smart WiringOptimal in combination with the Wire Cart for perfect workstation commissioning
Supply includes	Wire rail WT 35
Note	The gap dimension indicates the maximum diameter of the wire insulation.
Suitable for Model No.	4051.205 4051.210 4051.024 4051.036
Applications	For single wires with cross-section 1.5 mm ² (clearance 3.5 mm)
Packaging unit	1 pc(s).
Net weight	0.8 kg
Gross weight	0.84 kg
Customs tariff number	76169990

Features

Product description

Wire rail 1.5 mm² for the 15-fold rail system in the WT