

Rittal – The System.

Faster – better – everywhere.



AS 4051.237

Wire rail WT

State: 7/2/2026 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AS 4051.237 - Wire rail WT

The ready-cabled wires are fed to the WT 53 wire rail with a cross-section of 6.0 mm² by removal handling.



Features

Model No.	AS 4051.237
Product description	Busbar tightener for Perforex machining center BC and Perforex Milling Terminal MT, for easy processing of copper bars. Suitable for drilling and tapping.
Benefits	Project-related commissioning for downstream processes Project-related sorting of wires Optimal removal handling Rail system prepared for optimal workplace picking No wire sorting required Simplifies wiring process with step-by-step instructions in Eplan Smart Wiring Optimal in combination with the Wire Cart for perfect workstation commissioning
Supply includes	Wire rail WT 53
Note	The gap dimension indicates the maximum diameter of the wire insulation.
Suitable for Model No.	4051.205 4051.210 4051.024 4051.036
Applications	For single wires with cross-section 6 mm ² (clearance 5.3 mm)
Packaging unit	1 pc(s).

Features

Net weight	0.85 kg
Gross weight	1 kg
Customs tariff number	76169990
Product description	Wire rail 6.0 mm ² for the 15-fold rail system in the WT
