

Rittal – The System.

Faster – better – everywhere.



AS 4055.400

Hole punch, rectangular

State: 4/30/2026 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AS 4055.400 - Hole punch, rectangular for carbon steel

For punching rectangular cut-outs

Features

Model No.	AS 4055.400
Product description	For punching rectangular cut-outs. The hole punch is operated with a wrench or hydraulic punch.
Benefits	With side chute for waste No jamming of die
Supply includes	Die Stamp Tension bolts Lock nut Plastic case Thrust nut with ball bearing Adapter for hydraulics
Workable material	Carbon steel
Max. material thickness that can be machined for sheet steel	2 mm
Hydraulic operation	Yes
Manual operation	Yes
∅ hole punch	22 x 30 mm
Packaging unit	1 pc(s).
Net weight	0.807 kg
Gross weight	0.837 kg
Customs tariff number	82073010
ETIM 9	EC000156
ETIM 8	EC000156
ECLASS 8.0	21049047
Product description	Hole punch, rectangular for sheet steel