

Rittal – The System.

Faster – better – everywhere.



AS 4055.401

Hole punch, rectangular

State: 8/5/2025 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AS 4055.401 - Hole punch, rectangular for carbon steel

For punching rectangular cut-outs

Features

| | |
|--|---|
| Model No. | AS 4055.401 |
| Product description | For punching rectangular cut-outs. The hole punch is operated with a wrench or hydraulic punch. |
| Benefits | With side chute for waste No jamming of die |
| Supply includes | Die Stamp Tension bolts Lock nut Plastic case Thrust nut with ball bearing Adapter for hydraulics |
| Workable material | Carbon steel |
| Max. material thickness that can be machined for sheet steel | 2 mm |
| Hydraulic operation | Yes |
| Manual operation | Yes |
| Ø hole punch | 22 x 42 mm |
| Packaging unit | 1 pc(s). |
| Net weight | 0.731 |
| Gross weight | 0.909 |
| Customs tariff number | 82073010 |
| EAN | 4028177808461 |
| ETIM 9 | EC000156 |
| ETIM 8 | EC000156 |
| ECLASS 8.0 | 21049047 |