

Rittal – The System.

Faster – better – everywhere.



AS 4055.402

Hole punch, rectangular

State: 8/24/2025 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AS 4055.402 - Hole punch, rectangular for carbon steel

For punching rectangular cut-outs

Features

| | |
|--|---|
| Model No. | AS 4055.402 |
| Product description | For punching rectangular cut-outs. The hole punch is operated with a wrench or hydraulic punch. |
| Benefits | With side chute for waste No jamming of die |
| Supply includes | Die Stamp Tension bolts Lock nut Plastic case |
| Workable material | Carbon steel |
| Max. material thickness that can be machined for sheet steel | 2 mm |
| Hydraulic operation | Yes |
| □ hole punch | 45 x 92 mm |
| Packaging unit | 1 pc(s). |
| Net weight | 4.3 |
| Gross weight | 4.346 |
| Customs tariff number | 82073010 |
| EAN | 4028177808478 |
| ETIM 9 | EC000156 |
| ETIM 8 | EC000156 |
| ECLASS 8.0 | 21049047 |