


Rittal – The System.

Faster – better – everywhere.



AS 4055.463

Hole punch, heavy connectors

State: 7/8/2025 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AS 4055.463 - Hole punch, heavy connectors for carbon steel

For punching rectangular cut-outs for connectors

Features

| | |
|--------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model No. | AS 4055.463 |
| Product description | For punching rectangular cut-outs for connectors. The hole punch is operated with a hydraulic punch. |
| Benefits | With side chute for waste No jamming of die When the die and stamp are compressed, the mounting holes for connectors are marked on the metal sheet between them |
| Supply includes | Die Stamp Tension bolts Lock nut |
| Workable material | Carbon steel |
| Max. material thickness that can be machined for sheet steel | 2 mm |
| □ hole punch | 36 x 86 mm |
| Packaging unit | 1 pc(s). |
| Net weight | 3.6 |
| Gross weight | 3.648 |
| Customs tariff number | 82073010 |
| EAN | 4028177808539 |
| ETIM 9 | EC000156 |
| ETIM 8 | EC000156 |
| ECLASS 8.0 | 21049047 |