

Rittal – The System.

Faster – better – everywhere.



TS 4163.000 Threaded blocks

State: 4/26/2026 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TS 4163.000 - Threaded blocks

Used on enclosures and rails with rectangular 12.5 x 10.5 mm system punching with snap-off insertion aid, made from die-cast zinc.



Features

| | |
|-----------------------------|---|
| Model No. | TS 4163.000 |
| Product description | With snap-off insertion aid, made from die-cast zinc. |
| Installation options | <ul style="list-style-type: none">On the horizontal and vertical VX enclosure sectionOn the vertical TS, VX SE enclosure section via adapter rail for VX compatibilityOn the horizontal TS enclosure sectionOn the horizontal VX SE enclosure section, bottomOn the horizontal VX SE enclosure section top, in depthOn punched rails 23 x 23 mmOn mounting chassis 23 x 73 mmOn mounting chassis 45 x 88 mmOn 23 x 64 mm system chassisOn 23 x 73 mm system chassisOn 23 x 89 mm system chassis, stainless steelOn enclosures and rails with rectangular hole profile 12.5 x 10.5 mm |
| Dimensions | Thread: M8 |
| Suitable for enclosure type | <ul style="list-style-type: none">VXTSVX SE |
| Thread | M8 |
| Packaging unit | 50 pc(s). |
| Net weight | 0.4 kg |

Features

| | |
|-----------------------|----------------------------------|
| Gross weight | 0.461 kg |
| Customs tariff number | 73181692 |
| ETIM 9 | EC002358 |
| ETIM 8 | EC002358 |
| ECLASS 8.0 | 23110815 |
| Product description | TS Threaded block, for thread M8 |
