


Rittal – The System.

Faster – better – everywhere.



SZ 4172.000

Punched Rails, 23 x 23 mm

State: 5/31/2026 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SZ 4172.000 - Punched Rails, 23 x 23 mm for VX, TS, VX SE

Mounted on the horizontal and vertical enclosure sections using additional assembly components.



Features

| | |
|----------------------|--|
| Model No. | SZ 4172.000 |
| Material | Carbon steel |
| Surface finish | Zinc-plated |
| Length | 695 mm 27.4 " |
| Installation options | <p>In VX on vertical and horizontal enclosure section via TS mounting brackets.</p> <p>In VX SE on vertical enclosure section via mounting brackets in conjunction with adapter rail VX</p> <p>In VX SE on the horizontal profile/in the roof via mounting brackets in conjunction with adapter rail VX in depth</p> <p>On the vertical enclosure section: Directly via support brackets TS, via adapter rail for PS compatibility in conjunction with angle brackets, mounting brackets or support brackets PS.</p> <p>On the horizontal enclosure section: Directly via angle brackets, mounting brackets or support brackets PS</p> |
| Suitable for | <p>Enclosure type: VX TS VX SE</p> <p>Suitable for width or height or depth: 800 mm</p> |

Features

| | |
|-------------------------------------|--|
| Packaging unit | 12 pc(s). |
| Net weight | 5.088 kg |
| Gross weight | 5.45 kg |
| PCF/VE (cradle-to-gate) | 27.03 kg CO2 eq (Cat B) |
| Information regarding the PCF class | Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared |
| Customs tariff number | 73269098 |
| ETIM 9 | EC002620 |
| ETIM 8 | EC002620 |
| ECLASS 8.0 | 27189234 |
| Product description | SZ Punched rail 23 x 23 mm, for TS, SE, for WHD: 800 mm, L: 695 mm |

Approvals

| | |
|--------------|-----------------|
| Explanations | PCF-declaration |
|--------------|-----------------|