



# Rittal – The System.

Faster – better – everywhere.



## SZ 4178.000

## Punched Rails, 23 x 23 mm

State: 9/9/2025 (Source: [rittal.com/us-en](http://rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SZ 4178.000 - Punched Rails, 23 x 23 mm for VX, TS, VX SE

Mounted on the horizontal and vertical enclosure sections using additional assembly components.



## Features

Model No.	SZ 4178.000
Material	Carbon steel
Surface finish	Zinc-plated
Length	2,095 mm 82.5 "
Installation options	On the vertical enclosure section: Directly via support brackets TS, via adapter rail for PS compatibility in conjunction with angle brackets, mounting brackets or support brackets PS. On the horizontal enclosure section: Directly via angle brackets, mounting brackets or support brackets PS
Suitable for	Enclosure type: VX TS VX SE Suitable for width or height or depth: 2,200 mm
Packaging unit	6 pc(s).
Net weight	9.036
Gross weight	9.514
PCF/VE (cradle-to-gate)	36.3 kg CO2 eq (Cat B)

# Features

Information regarding the PCF class	Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared
Customs tariff number	73269098
EAN	4028177093287
ETIM 9	EC002620
ETIM 8	EC002620
ECLASS 8.0	27189234