

Rittal – The System.

Faster – better – everywhere.



TS 4309.000 Support Strip

State: 4/23/2026 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TS 4309.000 - Support Strip for VX, TS, VX SE, TP, AX

For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment.



Features

| | |
|----------------------------|--|
| Model No. | TS 4309.000 |
| Product description | For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment. |
| Technical specifications | 4.5 mm diameter hole on a 25 mm hole pattern |
| Material | Carbon steel |
| Surface finish | Zinc-plated |
| Supply includes | Assembly components |
| Length | 390 mm 15.4 " |
| Suitable for door width | 500 mm 19.7 " |
| Installation options VX | In door width 500 mm |
| Installation options VX SE | In door width 500 mm In enclosure depth 400 mm, on the inner mounting level, in conjunction with adaptor rail for VX compatibility |
| Installation options AX | In door width 500 mm, with 3-point locking system in the locking door In enclosure width 400 mm and in enclosure height 500 mm, in conjunction with rail for interior installation AX |

Features

| | |
|--|--|
| Installation options AX stainless steel | In enclosure width + 400 mm In enclosure height/width 500 mm |
| Installation options AX plastic | In door width 500 mm |
| Installation options for 3-part AX | Enclosure depth 573 mm |
| Installation options TS | In door width 500 mm In enclosure width/depth 400 mm on the inner mounting level |
| Installation options TP | In consoles for 3-part assembly, at the height of the enclosure cover, in conjunction with rail for interior installation for TP, compact enclosure HD |
| Installation options VX base/plinth, stainless steel | In base/plinth depth 500 mm, in conjunction with M6 hexagon socket screws and M6 nuts |
| Suitable for | Enclosure type: VX TS VX SE TP AX AX plastic AX wall-mounted housing, 3-part Width/depth: 400 mm Enclosure type: VX TS VX SE TP AX AX plastic AX wall-mounted housing, 3-part Width/depth: 15.7 " |
| Suitable for | VX base/plinth system, stainless steel |
| Packaging unit | 20 pc(s). |
| Net weight | 3.78 kg |
| Gross weight | 4.1 kg |
| PCF/VE (cradle-to-gate) | 15.2 kg CO2 eq (Cat B) |
| Information regarding the PCF class | Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared |

Features

| | |
|-----------------------|--|
| Customs tariff number | 73269098 |
| ETIM 9 | EC002620 |
| ETIM 8 | EC002620 |
| ECLASS 8.0 | 27189261 |
| Product description | TS support strip, for TS, VX SE, TP, AX for inner mounting level: for W/D: 400 mm, for door width: 500 mm, L: 390 mm |

Approvals

| | |
|--------------|-----------------|
| Explanations | PCF-declaration |
|--------------|-----------------|