

# Rittal – The System.

Faster – better – everywhere.



## TS 4695.000 Support Strip

State: 6/19/2026 (Source: [rittal.com/us-en](http://rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# TS 4695.000 - Support Strip for VX, TS, VX SE, TP, AX

For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment.



## Features

|   |  |
|---|--|
| Model No.                               | TS 4695.000  |
| Product description                     | For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment. |
| Technical specifications                | 4.5 mm diameter hole on a 25 mm hole pattern   |
| Material                                | Carbon steel   |
| Surface finish                          | Zinc-plated  |
| Supply includes                         | Assembly components  |
| Length                                  | 440 mm<br>17.3 "   |
| Installation options VX                 | In enclosure depth 500 mm  |
| Installation options VX SE              | In enclosure depth 500 mm, on the outer mounting level   |
| Installation options AX                 | In door width 500 mm, with cam lock<br>In door width 500 mm, with 3-point locking system, in the single-action door  |
| Installation options AX stainless steel | In door width 500 mm, in the single-action door, in conjunction with the punched door strip  |
| Installation options TS                 | In enclosure width/depth 500 mm, on the outer mounting level   |

# Features

|                                     |   |
|-------------------------------------|---|
| Installation options AE             | In enclosure width/height 500 mm, in conjunction with rail for interior installation AE   |
| Installation options TP             | In TP pedestal and one-piece console pedestal, in enclosure depth 500 mm, in conjunction with rail for interior installation for TP, compact enclosure HD |
| Suitable for                        | Enclosure type: VX<br>TS<br>VX SE<br>TP<br>AX<br>AE<br>Width/depth: 500 mm<br>Enclosure type: VX<br>TS<br>VX SE<br>TP<br>AX<br>AE<br>Width/depth: 19.7 "  |
| Packaging unit                      | 20 pc(s).   |
| Net weight                          | 4.4 kg  |
| Gross weight                        | 4.603 kg  |
| PCF/VE (cradle-to-gate)             | 21 kg CO2 eq (Cat B)  |
| Information regarding the PCF class | Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared                                      |
| Customs tariff number               | 73269098  |
| ETIM 9                              | EC002620  |
| ETIM 8                              | EC002620  |
| ECLASS 8.0                          | 27189261  |
| Product description                 | TS support strip, for VX, TS, VX SE, TP, for outer mounting level: for W/D: 500 mm, L: 440 mm   |

# Approvals

---

Explanations

PCF-declaration