Rittal – The System.

Faster – better – everywhere.



# TS 4696.000
# Support Strip

State: 11/26/2026 (Source: www.rittal.com/us-en)

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

# TS 4696.000 - Support Strip for VX, TS, VX SE, TP, AX

For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment.







## Features

| | |
|---|---|
| Model No. | TS 4696.000 |
| Product description | For simple attachment of cable ducts, cable conduit holders, contact hazard protection cover plates, equipment installed on the door, cable clamping and attachment. |
| Technical specifications | 4.5 mm diameter hole on a 25 mm hole pattern |
| Material | Carbon steel |
| Surface finish | Zinc-plated |
| Supply includes | Assembly components |
| Length | 540 mm<br>21.3 ″ |
| Installation options VX | In enclosure width/depth 600 mm |
| Installation options VX SE | In enclosure width/depth 600 mm, on the outer mounting level |
| Installation options AX | In door width 600 mm, with cam lock<br>In door width 600 mm, with 3-point lock system, in the hinged door |
| Installation options AX stainless steel | In door width 600 mm, in the single-action door, in conjunction with the punched door strip |
| Installation options PC | In enclosure width 600 mm, on the outer mounting level |
| Installation options IW | In enclosure width/depth 600 mm, on the outer mounting level |

© Rittal 2026

# Features

| | |
|---|---|
| Installation options TS | In enclosure width/depth 600 mm, on the outer mounting level |
| Installation options AE | In enclosure width/height 600 mm, in conjunction with rail for interior installation AE |
| Installation options TP | In consoles for 3-part assembly, at the height of the enclosure cover, in conjunction with rail for interior installation for TP, compact enclosure HD |
| Installation options VX Base | In base/plinth width/depth 600 mm on the base/plinth panels, in conjunction with base/plinth installation bracket |
| Suitable for | Enclosure type: VX<br>TS<br>VX SE<br>TP<br>PC<br>IW<br>AX<br>AE<br>Width/depth: 600 mm<br>Enclosure type: VX<br>TS<br>VX SE<br>TP<br>PC<br>IW<br>AX<br>AE<br>Width/depth: 23.6 ″ |
| Suitable for | VX base system |
| Packaging unit | 20 pc(s). |
| Net weight | 5.3 kg |
| Gross weight | 5.5 kg |
| PCF/VE (cradle-to-gate) | 25.64 kg CO2 eq (Cat B) |
| Information regarding the PCF class | Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared |
| Customs tariff number | 73269098 |
| ETIM 9 | EC002620 |

# Features

| | |
|---|---|
| ETIM 8 | EC002620 |
| ECLASS 8.0 | 27189261 |
| Product description | TS support strip, for VX, TS, VX SE, TP, for outer mounting level: for W/D: 600 mm, L: 540 mm |

# Approvals

| | |
|---|---|
| Explanations | PCF-declaration |