


Rittal – The System.

Faster – better – everywhere.



CM 5001.083 Cable clamp rail

State: 9/8/2025 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



CM 5001.083 - Cable clamp rail C-section, for mounting plates, for VX, TS, VX SE, TP

Provides strain relief for cable entries. The length of the cable clamp rail is matched to the width of the mounting plate. Three different installation situations are possible on the mounting plate with the mounting brackets included with the supply.

Features

Model No.	CM 5001.083
Product description	Provides strain relief for cable entries. The length of the cable clamp rail is matched to the width of the mounting plate. Three different installation situations are possible on the mounting plate with the mounting brackets included with the supply.
Material	Carbon steel
Surface finish	Zinc-plated
Supply includes	Incl. two mounting brackets and assembly screws.
Installation options	straight, at a distance of 23 mm from the mounting plate straight, at a distance of 10 mm from the mounting plate inclined, towards the mounting plate
Installation options VX Base	In base/plinth width/depth 1200 mm with installation on the base/plinth corner pieces, in conjunction with carbon steel hexagon socket screws
Installation options VX base/plinth, stainless steel	In base/plinth width 1200 mm, in conjunction with M6 hexagon socket screws and M6 nuts
Suitable for	VX base system VX base/plinth system, stainless steel
Dimensions	Length: 1,099 mm Length: 43.3 "

Features

Suitable for	Enclosure type: VX TS VX SE TP Width: = 1,200 mm Enclosure type: VX TS VX SE TP Width: = 47.2 ~
Packaging unit	1 pc(s).
Net weight	0.93
Gross weight	1.14
PCF/VE (cradle-to-gate)	1.7 kg CO2 eq (Cat B)
Information regarding the PCF class	Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared
Customs tariff number	73269098
EAN	4028177502970
ETIM 9	EC000322
ETIM 8	EC000322
ECLASS 8.0	27400604