

Faster – better – everywhere.





CM 5117.500 CM Compact System Enclosures

IT INFRASTRUCTURE SOFTWARE & SERVICES

State: 5/16/2024 (Source: rittal.com/us-en)

POWER DISTRIBUTION >> CLIMATE CONTROL



FRIEDHELM LOH GROUP

ENCLOSURES

CM 5117.500 - CM Compact System Enclosures

Housing with door made from sheet steel with mounting plate and open base to accommodate base plates. Protection category IP 55. A symbiosis of the enclosure benefits of Rittal compact enclosures, and the configuration diversity of the TS 8 baying enclosure system. Perforated mounting strips in the door for fast attachment of support strips, cable conduit holders and covers.



Features

Model No.	CM 5117.500
Material	Housing: Carbon steel, 1.5 mm
	Door: Carbon steel, 2.0 mm, all-round foamed-in PU seal
	Mounting plate: Carbon steel, 3.0 mm
Surface finish	Housing and door: Dipcoat primed, powder-coated on the outside,
	textured paint
	Mounting plate: Zinc-plated
Color	RAL 7035
Supply includes	Housing with hinged door(s)
	3-point locking system with double-bit insert
	Mounting plate
	Open base for individual cable entry
Protection category NEMA	NEMA 12 with selection of the appropriate base plate or trim pane
Protection category IP to EN 60 529	IP 55 with selection of the appropriate base plate or trim panel
IK code	IK08

Features

Dimensions	Width: 800 mm
	Height: 1,200 mm
	Depth: 400 mm
	Width: 31.5 ″
	Height: 47.2 ″
	Depth: 15.7 "
Dimensions of mounting plate (W	740 mm x 1,155 mm
x H)	29.1 ″ x 45.5 ″
Number of doors	1
Interchangeable door catch	Yes
Base material	Carbon steel
Packaging unit	1 pc(s).
Weight/packaging unit	71 kg
	156.5 lb.
Customs tariff number	94032080
EAN	4028177479777
E-Number Sweden	E3404464
ETIM 7.0	EC000261
ECLASS 8.0	27180101

Approvals

Approvals	UL + C-UL (listed)
Explanations	Declaration of conformity Declaration of conformity UK