

Rittal – The System.

Faster – better – everywhere.



DK 5302.016 Air Baffle Plate

State: 6/1/2026 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



DK 5302.016 - Air Baffle Plate for VX IT 19" standard profile rail

To separate the hot/cold zones within an enclosure with aisle containment or when using an LCP system.



Features

Model No.	DK 5302.016
Benefits	For targeted increase of energy efficiency of air conditioning Vertical brush strip for collision-free shielding with installed bar systems on the outer mounting level.
Applications	To separate the hot/cold zones within an enclosure with aisle containment or when using an LCP system.
Material	Carbon steel Blanking panel: Plastic, UL 94-HB, halogen-free Brush strip: Plastic, UL 94-HB
Surface finish	Spray-finished
Color	RAL 9005
Supply includes	2 vertical trim panels 2 horizontal trim panels 4 brush strips 4 cellular PU foam pieces Assembly components

Features

Mounting tip	<p>For partitioning, the vertical trim panels with brush strips can be mounted to both the front and rear 19" profile rails.</p> <p>The horizontal trim panels with brush strips can only be mounted on the front 19" profile rails.</p> <p>482.6 mm (19") mounting cut-outs integrated within the partitioning areas may optionally be sealed with the supplied blanking panels, or used to install additional components or for cable routing. Please see the product-specific scope of supply.</p>
Suitable for	<p>Width: = 600 mm</p> <p>Height: = 2,000 mm</p> <p>Width: = 23.6 "</p> <p>Height: = 78.7 "</p>
Packaging unit	1 pc(s).
Net weight	2.06 kg
Gross weight	2.66 kg
PCF/VE (cradle-to-gate)	10.1 kg CO2 eq (Cat B)
Information regarding the PCF class	Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared
Customs tariff number	56090000
ETIM 9	EC000331
ECLASS 8.0	27189272
Product description	Air baffle plate, for VX IT 19" mounting angles, standard, to separate the hot/cold zones within an enclosure with aisle containment or when using an LCP system. WxH: 600x2000 mm, RAL 9005