


# Rittal – The System.

Faster – better – everywhere.



## PC 5366.450 PC enclosure system

State: 8/13/2025 (Source: [rittal.com/us-en](http://rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# PC 5366.450 - PC enclosure system

Secure accommodation of all PC components, from monitors, to PCs and keyboards. Extremely simple to use and modern design. Complete protection from humidity and dirt, temperature fluctuations and unauthorized access.



## Features

Model No.	PC 5366.450
Version	with keyboard drawer and large mounting compartment
Product description	Secure accommodation of all PC components, from monitors, to PCs and keyboards. For ultimate ease of operation in a contemporary design. Complete protection from humidity and dirt, temperature fluctuations and unauthorized access.
Material	Housing, door, rear door, mounting compartment, supports: carbon steel Handles, decorative trim panels: Plastic Door trim panels: Aluminum Mounting compartment, support: Carbon steel
Surface finish	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting compartment, support: powder-coated
General color	RAL 7035
Color	Housing, door, decorative trim panels, supports: RAL 7035 Handle: RAL 7015 Monitor field, door center section: RAL 7015

# Features

Supply includes	Housing, door, rear door Base Plates Keyboard drawer Mounting compartment, large
Dimensions	Width: 600 mm Height: 1,600 mm Depth: 636 mm Width: 23.6 " Height: 63 " Depth: 25 "
Protection category IP to IEC 60529	IP 55
Protection category NEMA	NEMA 12
Type rating according to UL 50E	Type 1 Type 12
Max. keyboard dimensions (WxHxD)	480 x 70 x 260 mm 18.9 x 2.76 x 10.2 "
Base material	Carbon steel
Packaging unit	1 pc(s).
Net weight	89.5
Gross weight	92
PCF/VE (cradle-to-gate)	371.5 kg CO2 eq (Cat B)
Information regarding the PCF class	Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared
EAN	4028177959453
ETIM 9	EC002502
ECLASS 8.0	27180501

## Approvals

Approvals	UL + C-UL (listed)
-----------	--------------------

# Approvals

---

Certificates

Surface finish

---

Explanations

Declaration of conformity

Declaration of conformity UK