

Rittal – The System.

Faster – better – everywhere.



DK 5501.695

Component Shelf, Static Installation

State: 4/27/2026 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



DK 5501.695 - Component Shelf, Static Installation for VX IT, TS IT, TE, TX CableNet

For static installation between two 19" mounting levels.



Features

| | |
|----------------------|--|
| Model No. | DK 5501.695 |
| Benefits | Tool-free, time-saving one-person assembly |
| Applications | Depth-variable to adapt to individual distances between levels |
| Material | Carbon steel |
| Surface finish | Spray-finished |
| Color | RAL 9005 |
| Supply includes | Assembly components |
| Installation options | 482.6 mm (19") L-profile rails, front and rear 482.6 mm (19") mounting frames, front and rear |
| Applications | For larger spacing between levels, it is necessary to reduce the pre-mounted spacing between levels; load capacity 100 kg. |
| Load capacity | 100 kg |
| Dimensions | Width: 484 mm Width: 19.1 " |
| Suitable for | Enclosure type: VX IT TS IT TE |

Features

| | |
|-------------------------------------|--|
| Distance between levels | 400 - 600 mm 15.7 - 23.6 " |
| Packaging unit | 1 pc(s). |
| Net weight | 5.427 kg |
| Gross weight | 5.73 kg |
| PCF/VE (cradle-to-gate) | 21 kg CO2 eq (Cat B) |
| Information regarding the PCF class | Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared |
| Customs tariff number | 73269098 |
| ETIM 9 | EC002620 |
| ECLASS 8.0 | 27189261 |
| Product description | DK Component shelf, WxH: 484 mm x 1 U, 100 kg, distance between levels: 400-600 mm, depth-variable, RAL 9005 |