Rittal – The System.

Faster – better – everywhere.





SE 5834.680 VX SE enclosure system

State: 6/9/2025 (Source: rittal.com/us-en)



SE 5834.680 - VX SE enclosure system IP 66/NEMA 4

Individual carbon steel enclosure with stable enclosure body, two integrated mounting levels, screw-fastened rear panel and door. Roof and sides from a single piece with roll-formed frame. Fully compatible with the VX25 baying system. Increases efficiency as side panels do not have to be mounted. High level of protection to IP 66/NEMA 4.







Features

Model No.	SE 5834.680
Material	Housing: Carbon steel, 1.5 mm
	Door: Carbon steel, 2.0 mm
	Rear wall: carbon steel, 1.5 mm
	Base: Carbon steel, 1.5 mm
	Mounting panel: Carbon steel, 3.0 mm
Surface finish	Housing, door and rear panel: Dipcoat-primed, powder-coated on the
	outside, textured paint
	Mounting panel: Zinc-plated
	Base: Dipcoat-primed and powder-coated, textured paint
Color	RAL 7035
Supply includes	Housing, solid top and sides
	Door(s)
	Door hinged on the right, may be swapped to the left
	Mounting panel
	Base, gland plate(s)
	Rear panel, detachable
	Lock: 3 mm double-bit
	2 punched rails, 18 x 39 mm

© Rittal 2025 2

Features

Dimensions	Width: 800 mm
	Height: 2,000 mm
	Depth: 600 mm
	Width: 31.5 "
	Height: 78.7 "
	Depth: 23.6 "
Dimensions of mounting plate (W	699 mm x 1,896 mm
x H)	27.5 ″ x 74.6 ″
Protection category IP to EN 60 529	IP 66
Protection category NEMA	NEMA 4
Type rating according to UL 50E	Type 1
	Type 2
	Type 3
	Type 3R
	Type 4
	Type 12
IK code	IK10
Number of doors	1
Base material	Carbon steel
Packaging unit	1 pc(s).
Net weight	148
Gross weight	152
PCF per pack (cradle-to-gate)	579.1 kg CO2 eq (Cat B)
Note on PCF category	Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared
EAN	4028177959316
ETIM 9	EC000261
ECLASS 8.0	27180101

© Rittal 2025 3

Approvals

Approvals	UL + C-UL (listed)
Certificates	Surface finish Protection category
Explanations	Declaration of conformity Declaration of conformity UK

© Rittal 2025