Rittal – The System.

Faster – better – everywhere.





SE 5858.600 VX SE enclosure system

POWER DISTRIBUTION >> CLIMATE CONTROL

State: 7/22/2025 (Source: rittal.com/us-en)



IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

ENCLOSURES

SE 5858.600 - VX SE enclosure system Stainless steel

Individual stainless steel enclosure with stable enclosure body, two integrated mounting levels, screw-fastened rear panel and door. Roof and sides from a single piece with roll-formed frame. Fully compatible with the VX25 baying system. Enclosure widths ranging from 600 to 1200 mm. Increases efficiency as side panels do not have to be mounted.



Features

| Model No. | SE 5858.600 |
|-----------------|---|
| Material | Housing: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed Door: Stainless steel 1.4301 (AISI 304), 2.0 mm, exterior brushed Rear panel: Stainless steel 1.4301 (AISI 304), 1.5 mm, exterior brushed Base plates: Stainless steel 1.4301 (AISI 304), 1.5 mm Mounting panel: Carbon steel, 3.0 mm |
| Surface finish | Housing, door and rear panel: Brushed, grain 400 Base plates: Uncoated Mounting panel: Zinc-plated |
| Supply includes | Housing, solid top and sides Door(s) Right-hand door catch on single-door enclosures may be swapped to the left Rear panel, detachable Mounting panel Base Plates Lock: 3 mm double-bit 2 punched rails, 18 x 39 mm |

Features

| Dimensions | Width: 1,200 mm Height: 1,200 mm Depth: 500 mm Width: 47.2 ″ Height: 47.2 ″ Depth: 19.7 ″ |
|---|--|
| Dimensions of mounting plate (W x H) | 1,099 mm x 1,096 mm 43.3 ˝ x 43.1 ˝ |
| Protection category IP to EN 60 529 | IP 55 |
| Protection category NEMA | NEMA 12 |
| Type rating according to UL 50E | Type 1 Type 2 Type 3 Type 3R Type 12 |
| IK code | IK10 |
| Number of doors | 2 |
| Note | Due to the hardness of the material, we recommend using metal multi-tooth screws 2486.400 for the interior installation. |
| Base material | Stainless steel 1.4301 (AISI 304) |
| Packaging unit | 1 pc(s). |
| Net weight | 115 |
| Gross weight | 129.8 |
| EAN | 4028177970274 |
| ETIM 9 | EC000261 |
| ETIM 8 | EC000261 |
| ECLASS 8.0 | 27180101 |

Approvals

Approvals

| Approvals | UL + C-UL (listed) |
|--------------|---|
| Certificates | Surface finish Protection category |
| Explanations | Declaration of conformity Declaration of conformity UK |