

Rittal – The System.

Faster – better – everywhere.



CP 6372.553 Comfort Panel

State: 7/1/2026 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



CP 6372.553 - Comfort Panel

Aluminum housing, high thermal conductivity for optimum passive heat dissipation. Low weight coupled with high stability. Protection category IP 65 to IEC 60 529.



Features

| | |
|-----------------|---|
| Model No. | CP 6372.553 |
| Version | Support arm connection Ø 130 mm |
| Benefits | Aluminum housing, high thermal conductivity for optimum passive heat dissipation. Low weight coupled with high stability Compatible with all Rittal stand and support arm systems |
| Material | Housing: Extruded aluminum section Corner pieces: Die-cast zinc Corner protectors: Plastic |
| General color | Natural anodized |
| Color | Housing: Natural anodized. Corner pieces: RAL 7035 Corner protectors: Similar to RAL 7024 |
| Supply includes | Enclosure with cut-out for support arm connection 3 mm double-bit lock insert may be exchanged for 41 mm lock inserts, plastic handles and T handles, type C Seals and assembly components for front panels Rear panel screwed, enclosure hinged at the front with side double-bit lock insert |

Features

| | |
|-------------------------------------|---|
| Dimensions | Width: 628.5 mm Height: 608.5 mm Depth: 209 mm Width: 24.7 " Height: 24 " Depth: 8.23 " |
| Installation depth | 191 mm 7.52 " |
| Protection category IP to IEC 60529 | IP 65 |
| Protection category NEMA | NEMA 12 |
| Suitable for front panel width | 520 mm 20.5 " |
| Suitable for front panel height | 500 mm 19.7 " |
| Version | Service access from rear |
| Note | The support arm connection may be swapped over by rotating the enclosure |
| Base material | Aluminum |
| Lock | Lock version: Sickle-shaped locking nose No. of locks: 2 Lock Insert: 3 mm double-bit |
| Packaging unit | 1 pc(s). |
| Net weight | 17 kg |
| Gross weight | 18.1 kg |
| Customs tariff number | 94032080 |
| ETIM 9 | EC002504 |
| ECLASS 8.0 | 27180505 |
| Product description | CP Compact Panel, for front panel BH 520x500 mm, installation depth 191 mm, Extruded aluminum section, Support arm connection Ø 130 mm, Screw-fastened rear panel |

Approvals

Approvals

UL + C-UL (listed)

Explanations

Declaration of conformity

Declaration of conformity UK