

Rittal – The System.

Faster – better – everywhere.



IW 6900.301

PC Enclosure Systems

State: 5/8/2025 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



IW 6900.301 - PC Enclosure Systems Housing for Tower PC

Housing for commercially available tower PCs.

Features

Model No.	IW 6900.301
Version	Roof prepared for mounting worktop or for mounting underneath surfaces Roof prepared for mounting cast feet or for mounting on surfaces
Product description	Standard, commercially available PC towers, up to W/H/D: 250 x 530 x 600 mm (max. 20 kg) can be securely attached to the floor or bolted to the door by means of an enclosed retaining strap. The rear interfaces of the PC are easily accessible with the door open. Because the filter fan unit is already pre-installed, the housing is ready for immediate use.
Material	Housing: Carbon steel Door: Carbon steel Design strips: Aluminum
Surface finish	Housing: Powder-coated, textured paint Door: Powder-coated
Color	Housing: RAL 7035 Door: RAL 7015 Design strips: RAL 7035
Supply includes	Housing of all-round solid construction R/h door catch Door with base screw-fastened on the inside Side cam lock Double-bit lock insert Rear panel with two cut-outs for use of the connector gland supplied loose Cable gland M20, brass, nickel-plated Outlet filter fitted in left side panel Fan-and-filter unit fitted in right side panel, 55 m³/h, 230 V, 50/60 Hz

Features

Dimensions	Width: 760 mm Height: 760 mm Depth: 300 mm Width: 29.9 “ Height: 29.9 “ Depth: 11.8 “
Protection category IP to IEC 60 529	IP 54 in conjunction with connector gland supplied loose
Protection category NEMA	NEMA 12 in conjunction with connector gland supplied loose
Base material	Aluminum
Packaging unit	1 pc(s).
Net weight	34.2
Gross weight	36
EAN	4028177937598
ECLASS 8.0	27180501

Approvals

Explanations	Declaration of conformity
--------------	---------------------------