Rittal – The System.

Faster - better - everywhere.





DK 7030.040 CMC III I/O Units

State: 12/8/2025 (Source: rittal.com/us-en)



DK 7030.040 - CMC III I/O Units

Monitoring of up to eight digital inputs and control of up to four relays.







Features

| DK 7030.040 |
|--|
| In the software, the relays can be linked to measurement values so that they are switched under certain circumstances. This allows devices to be monitored and messages to be forwarded. Cannot be operated with the Processing Unit Compact. |
| Fast connection and automatic detection via plug & play Minimal space requirements due to high concentration of inputs and outputs |
| Automatic bus sequence with consecutive numbering by the processing unit Power is supplied via the CAN bus interface. Status display via integral LED Inputs for ground-free signals Relay output (changeover contact) can handle loads of up to 24 V (DC)/1 A |
| Plastic Front: Smooth Housing: Textured |
| Housing: RAL 7035 Front: RAL 9005 |
| |

© Rittal 2025

Features

| he Processing Unit Compact |
|----------------------------|
| |
| |
| he Processing Unit Compact |
| he Processing Unit Compact |
| he Processing Unit Compact |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |

Approvals

| Approvals UL + C-UL (listed) | Approvals | UL + C-UL (listed) |
|------------------------------|-----------|--------------------|
|------------------------------|-----------|--------------------|

© Rittal 2025 3

Approvals

Explanations

Manufacturer's declaration Declaration of conformity

© Rittal 2025 4