Rittal – The System.

Faster – better – everywhere.



DK 7030.093

CMC III CAN bus connection cable

State: 11/6/2026 (Source: www.rittal.com/us-en)

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

DK 7030.093 - CMC III CAN bus connection cable

Connects CAN bus units to information and power distribution systems.

Features

Model No.	DK 7030.093
Product description	For cabling the PU with the CAN bus sensors III, units III, control units III as a bus, and also with each other. The different lengths allow the CMC III system to be adapted to different applications and specifically configured.
Applications	For connecting the CAN bus units. Information and power distribution systems of the individual CAN bus units.
Length	2 m 78.7 ″
Dimensions	Length: 2 m Length: 78.7 ″
Interfaces/connections	Connector (type): RJ45RJ45
Operating temperature range	0 °C...55 °C 32 °F...131 °F
Ambient humidity (non-condensing)	5...95 %
Packaging unit	1 pc(s).
Net weight	0.07 kg
Gross weight	0.081 kg
CRA risk class	Default (Low Risk)
Customs tariff number	85444290
ETIM 9	EC000313
ECLASS 8.0	27189253
Product description	DK CMC III CAN bus connection cable, L: 2 m, type: RJ45