

Rittal – The System.

Faster – better – everywhere.



DK 7030.550 CMC III CAN bus DRC

State: 3/13/2026 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



DK 7030.550 - CMC III CAN bus DRC

To connect a RFID controller.

Rittal – The System.

Faster – better – worldwide.



Installationsanleitung und Kurz-Bedienungsanleitung
Installation Guide and Short User's Guide
Notice d'installation et notice d'utilisation succincte



Features

Model No.	DK 7030.550
Version	The CAN bus DRC is required for connecting the RFID system to the CMC III. It connects the RFID controller to the CAN bus of the CMC III.
Product description	With the CMC III CAN bus DRC, the RFID controller can be connected to the CMC III system. One RFID controller can be connected to each CMC III CAN bus DRC. One external power supply is required for each CMC III CAN bus DRC.
Benefits	Fast connection and automatic detection via plug & play Graphical representation of the 19" equipment in the enclosure on the web interface of the CMC III
Applications	Managing the 19" equipment via the DRC system in enclosures in the fields of IT, industry and buildings technology.

Features

Function principle	Settings can be made via the CMC III Processing Unit Status display via integral LED The current measurements can be called up via the CMC III interface using the browser, SNMP or OPC-UA, and adjustments made Automatic alarm messages by e-mail, SMS or SNMP trap if a limit value is violated
Material	Plastic Front: Smooth Housing: Textured
Color	Housing: RAL 7035 Front: RAL 9005
Supply includes	CMC III CAN bus DRC Installation and Short User's Guide Assembly components for surfaces Mounting clips for support rails Mounting accessories
Interface bus system	2 x RJ45 CAN bus
Interfaces	RJ45
Quantity of participants PU compact (max.)	2
Quantity of participants PU (max.)	4
Note	For each CAN bus DRC, an additional power pack 7030.060 is required.
Dimensions	Width: 138 mm Height: 40 mm Depth: 132 mm Width: 5.43 " Height: 1.57 " Depth: 5.2 "
Operating temperature range	0 °C...55 °C 32 °F...131 °F
Ambient humidity (non-condensing)	5...95 %
Packaging unit	1 pc(s).

Features

Net weight	0.336 kg
Gross weight	0.604 kg
Customs tariff number	85176200
ETIM 9	EC002627
ECLASS 8.0	27189253
Product description	DK CMC III CAN bus DRC, WHD: 138x40x132 mm

Approvals

Explanations	Declaration of conformity
--------------	---------------------------