Rittal - The System.

Faster - better - everywhere.





DK 7030.571 CMC III LTE Unit

State: 11/17/2025 (Source: rittal.com/us-en)



DK 7030.571 - CMC III LTE Unit

The CMC III LTE unit reliably informs about alarm messages via ISDN or LTE via SMS.

Features

Model No.	DK 7030.571
Product description	For establishing a redundant transmission path or, if no network infrastructure is available, for alarm forwarding. The alarm message is sent as an SMS. Coverage of LTE (4G), UMTS (3G), and GSM (2G) with automatic toggle function, see bands, and frequencies. A standard, commercially available SIM card must be provided by the customer.
Technical specifications	The CMC III LTE-Unit can be used in 4G, 3G and 2G mobile networks in these frequency ranges: 4G LTE band 1 (2100 MHz) 4G LTE band 3 (1800 MHz) 4G LTE band 8 (900 MHz) 4G LTE band 20 (800 MHz) 4G LTE band 28 (700 MHz) 3G UMTS band 1 (2100 MHz) 3G UMTS band 8 (900 MHz) 2G GSM (900 MHz) 2G GSM (1800 MHz)
Material	Plastic
Color	Front: RAL 9005 Housing: RAL 7035
Supply includes	CMC III LTE Unit RJ12 cable Antenna with magnetic stand
Serial interface	2 x RJ12
Dimensions	Width: 138 mm Height: 40 mm Depth: 132 mm Width: 5.43 " Height: 1.57 " Depth: 5.2 "

© Rittal 2025

Features

Operating temperature range	0 °C55 °C
	32 °F131 °F
Storage temperature range	45 °C85 °C
	113 °F185 °F
Packaging unit	1 pc(s).
Net weight	0.6
Gross weight	0.645
Customs tariff number	85176200
EAN	4028177926011
ETIM 9	EC002627
ECLASS 8.0	27189253

Approvals

Explanations	Declaration of conformity
	Declaration of conformity UK

© Rittal 2025 3