

Rittal – The System.

Faster – better – everywhere.



DK 7320.630 CMC III Sensors

State: 7/9/2025 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



DK 7320.630 - CMC III Sensors

To monitor a range of parameters in enclosures or rooms.

Features

Model No.	DK 7320.630
Version	Leak sensor
Product description	CMC III sensors are used to monitor the physical environment and can be directly connected to the PU by an RJ45 CAN bus connection cable. The sensors can also be interconnected as a bus.
Benefits	Fast connection and automatic detection via plug & play Power is supplied via the CAN bus interface.
Applications	Enclosure monitoring in IT, industry and facility management Monitoring enclosures, rooms and containers in the field of IT.
Function principle	Settings can be made via the CMC III Processing Unit The sensor is mounted with the optical element towards the base. The sensor monitors the base for liquids (leakage) with an optical sensor.
Material	Plastic Front: Smooth Housing: Textured
Color	Housing: RAL 7035
Supply includes	Sensor Mounting panel Assembly components Connection cable with connector Assembly components
Connection to the CAN bus	Indirectly via CMC III Can-Bus Interfaces
Interfaces	RJ12
Quantity of participants PU compact (max.)	4
Quantity of participants PU (max.)	32

Features

Measuring technique	Optical
Dimensions	Width: 85 mm Height: 20 mm Depth: 18 mm Width: 3.35 “ Height: 0.79 “ Depth: 0.71 “
Operating temperature range	5 °C...45 °C 41 °F...113 °F
Ambient humidity (non-condensing)	5...95 %
Packaging unit	1 pc(s).
Net weight	0.09
Gross weight	0.095
Customs tariff number	85319000
EAN	4028177438590
ETIM 9	EC002627
ECLASS 8.0	27189253

Approvals

Explanations	Declaration of conformity
--------------	---------------------------