


Rittal – The System.

Faster – better – everywhere.



DK 7320.700

Handles, electromagnetic

State: 7/19/2025 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



DK 7320.700 - Handles, electromagnetic for CMC III and IoT interface

Handles can be integrated into various enclosure systems.

Features

Model No.	DK 7320.700
Version	Ergoform-S handle
Product description	For control and monitoring purposes using a central CMC III and IoT interface control unit.
Benefits	Autonomous access management with release of handle by means of a numeric code and transponder card Rights and remote opening are administered via the network Integrated web interface and link to central management systems via the control unit Log of all door openings with time stamp
Applications	Central access management across the network without keys or locking system Stand-alone network enclosures containing sensitive IT systems Data center with increased security requirements or colocation/ hosting applications
Color	RAL 7035
Supply includes	Connection cable (3 m) with RJ 12 connector.
Lock type	Electromagnetic
Rated current max.	0.1 A
Quantity of participants per IoT interface (max.)	16
Quantity of participants PU compact (max.)	2
Quantity of participants PU (max.)	16
Number subscribers per PDU note	Max. 5 pcs for power supply via PoE

Features

Operating temperature range	5 °C...40 °C 41 °F...104 °F
Packaging unit	1 pc(s).
Net weight	0.76
Gross weight	0.76
Customs tariff number	83024110
EAN	4028177367470
ETIM 9	EC000327
ECLASS 8.0	27409217