Rittal – The System.

Faster – better – everywhere.



AX_IT 7647.400

AX IT Nano Data Center wall-mounted enclosure

State: 11/24/2026 (Source: www.rittal.com/us-en)

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

AX_IT 7647.400 - AX IT Nano Data Center wall-mounted enclosure

Designer wall-mounted enclosure IT with 19" swing frame for vertical and horizontal mounting.





Features

Model No.	AX IT 7647.400
Version	IT enclosure for use in industrial environments Pre-configured
Benefits	Pre-configured enclosure to accommodate 482.6 mm (19") IT components Compact design with maximum usable interior volume The welded enclosure structure guarantees a high level of physical protection (up to IP 54) Vertical (top) and horizontal (front) assembly for deep and shallow IT components Interchangeable door catch Compatible with the AX wall-mounted enclosure system
Applications	IT enclosure for use in industrial environments
Material	Carbon steel
Surface finish	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Interior fittings: zinc-plated
Color	RAL 7035
Supply includes	Housing with hinged door Swing frame, 482.6 mm (19"), fitted Cam lock with 3 mm double-bit insert Gland plate

Features

Height units	11 U 4 U
Dimensions	Width: 600 mm Height: 800 mm Depth: 400 mm Width: 23.6 ″ Height: 31.5 ″ Depth: 15.7 ″
Position door catch	right, may be swapped to the left
Installation options	For vertical mounting For horizontal mounting
Note	Special design available on request
Lock	Lock version: Cam with 3 mm double-bit lock insert No. of locks: 2
Protection category	Protection category up to IP 54 possible, depending on the optionally selected filter fan
No. of locks	2
Packaging unit	1 pc(s).
Net weight	35.5 kg
Gross weight	36 kg
Customs tariff number	94032080
Product description	AX IT Nano DC wall-mounted distributor, pre-assembled, installation height for components 565 mm vertical / 250 mm horizontal, with 19" swing frame, WHD: 600x800x400 mm, with hinged door

Approvals

Approvals	UL + C-UL (listed)
Explanations	Declaration of conformity