Rittal - The System.

Faster – better – everywhere.





DK 7709.135 Wall-mounted enclosures EL, 3-part

State: 11/29/2025 (Source: rittal.com/us-en)



DK 7709.135 - Wall-mounted enclosures EL, 3-part with punched rails and profile rails, depth-variable

Wall-mounted housing 3-part, pre-configured with: Solid flange plate, top and bottom, punched rails, C rails, wall mounting bracket. Protection category IP 55.

Features

Model No.	DK 7709.135
Version	Wall-mounted housing IT with punched rails and profile rails, depth-variable
Product description	Wall-mounted enclosure with hinged door provides optimum accessibility.
Material	Wall and hinged part: Carbon steel, 1.5 mm Viewing window: Single-pane safety glass, 3 mm
Surface finish	Powder-coated
General color	RAL 7035
Color	Wall and hinged part: RAL 7035 Viewing door: RAL 7035/7015 (slate gray)
Supply includes	Wall section closed at top and bottom with flange (gland) plate, two vertical mounting rails and horizontal C-profile rails for cable clamping. Hinged part with 25 mm pitch pattern in the front and rear frame, two 482.6 mm (19") profile angles at the front, fully depth adjustable 4 wall mounting brackets 10 mm Designer viewing door 1 enclosure key double bit no. 5 Mini-comfort handle for lock inserts Security lock 3524 E
Height units	9 U

© Rittal 2025 2

Features

Width: 600 mm
Height: 478 mm
Depth: 473 mm
Width: 23.6 "
Height: 18.8 "
Depth: 18.6 "
420 mm
16.5 ″
Clearance width: 502 mm
Clearance height: 415 mm
Clearance width: 19.8 ″
Clearance height: 16.3 "
316 mm
12.4 ″
135 mm
F 0.4 "
5.31 ″
1K08
IK08
IK08 450 N
IK08 450 N 101.164 lbf.
IK08 450 N 101.164 lbf. Carbon steel
IK08 450 N 101.164 lbf. Carbon steel IP 55
IK08 450 N 101.164 lbf. Carbon steel IP 55 1 pc(s).
IK08 450 N 101.164 lbf. Carbon steel IP 55 1 pc(s). 29.45
IK08 450 N 101.164 lbf. Carbon steel IP 55 1 pc(s). 29.45 31
IK08 450 N 101.164 lbf. Carbon steel IP 55 1 pc(s). 29.45 31 94032080

© Rittal 2025 3

Approvals

Approvals

UL + C-UL (listed)

© Rittal 2025 4