Rittal - The System.

Faster – better – everywhere.





DK 7712.135 Wall-mounted enclosures EL, 3-part

State: 11/28/2025 (Source: rittal.com/us-en)



DK 7712.135 - Wall-mounted enclosures EL, 3-part with punched rails and profile rails, depth-variable

Wall-mounted housing 3-part, pre-configured with: Solid flange plate, top and bottom, punched rails, C rails, wall mounting bracket. Protection category IP 55.

Features

Model No.	DK 7712.135
Version	Wall-mounted housing IT
	with punched rails and profile rails, depth-variable
Product description	Wall-mounted enclosure with hinged door provides optimum accessibility.
Material	Wall and hinged part: Carbon steel, 1.5 mm
	Viewing window: Single-pane safety glass, 3 mm
Surface finish	Powder-coated
General color	RAL 7035
Color	Wall and hinged part: RAL 7035
	Viewing door: RAL 7035/7015 (slate gray)
Supply includes	Wall section closed at top and bottom with flange (gland) plate, two vertical mounting rails and horizontal C-profile rails for cable clamping.
	Hinged part with 25 mm pitch pattern in the front and rear frame,
	two 482.6 mm (19") profile angles at the front, fully depth adjustable
	4 wall mounting brackets 10 mm
	Designer viewing door
	1 enclosure key double bit no. 5
	Mini-comfort handle for lock inserts
	Security lock 3524 E
Height units	12 U

© Rittal 2025 2

Features

dth: 600 mm
ight: 612 mm
pth: 473 mm
dth: 23.6 "
ight: 24.1 ″
pth: 18.6 "
0 mm
.5 ″
earance width: 502 mm
earance height: 549 mm
earance width: 19.8 ″
earance height: 21.6 ″
6 mm
.4 ″
5 mm
31 ″
08
08 0 N
0 N
0 N 4.885 lbf.
0 N 4.885 lbf. rbon steel
0 N 4.885 lbf. rbon steel 55
0 N 4.885 lbf. rbon steel 55 oc(s).
0 N 4.885 lbf. rbon steel 55 oc(s).
0 N 4.885 lbf. rbon steel 55 oc(s).
0 N 4.885 lbf. rbon steel 55 oc(s)2

© Rittal 2025 3

Approvals

Approvals

UL + C-UL (listed)

© Rittal 2025 4