

# Rittal – The System.

Faster – better – everywhere.



## CP 8015.400 Comfort Panel

State: 6/10/2026 (Source: [rittal.com/us-en](http://rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# CP 8015.400 - Comfort Panel

Operating housing in a stylish / slimline design made from extruded aluminium sections for effective heat dissipation, with support arm cut-out Ø 130 mm or rectangular 120 x 65 mm to fit support arm system CP 60 / 120 / 180, service access from the front or rear, uniform all-round mounting channels for individual installation of accessories without machining, protection category IP 65. For the North American market, we have enhanced our product offerings to include the below additional size options.

## Features

Model No.	CP 8015.400
Benefits	Aluminum housing, high thermal conductivity for optimum passive heat dissipation. Low weight coupled with high stability Compatible with all Rittal stand and support arm systems
Material	Housing: Extruded aluminum section Corner pieces: Die-cast zinc Corner protectors: Plastic Housing: Extruded aluminum section Corner pieces: Die-cast zinc
Color	Housing: Natural anodized. Corner pieces: RAL 7035 Corner protectors: Similar to RAL 7024
Supply includes	Seals and assembly components for front panels
Suitable for front panel width	400 mm 15.7 "
Note	The support arm connection may be swapped over by rotating the enclosure 3 mm double-bit lock insert may be exchanged for 41 mm lock inserts, plastic handles and T handles, type C
OUT_SUITABLE_FOR_FRONT_PAN EL_HEIGHT	300 mm 11.8 "
Packaging unit	1 pc(s).
Net weight	27.399 lb

# Features

---

Gross weight	27.399 lb
Customs tariff number	9403200082

---

# Approvals

---

Approvals	UL + C-UL (listed)
-----------	--------------------