

Rittal – The System.

Faster – better – everywhere.



CP 8015.401 Comfort Panel

State: 4/5/2026 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



CP 8015.401 - Comfort Panel

Operating housing in a stylish / slimline design made from extruded aluminium sections for effective heat dissipation, with support arm cut-out Ø 130 mm or rectangular 120 x 65 mm to fit support arm system CP 60 / 120 / 180, service access from the front or rear, uniform all-round mounting channels for individual installation of accessories without machining, protection category IP 65. For the North American market, we have enhanced our product offerings to include the below additional size options.

Features

| | |
|---|---|
| Model No. | CP 8015.401 |
| Benefits | Aluminum housing, high thermal conductivity for optimum passive heat dissipation. Low weight coupled with high stability Compatible with all Rittal stand and support arm systems |
| Material | Housing: Extruded aluminum section Corner pieces: Die-cast zinc Corner protectors: Plastic |
| Color | Housing: Natural anodized. Corner pieces: RAL 7035 Corner protectors: Similar to RAL 7024 |
| Supply includes | Seals and assembly components for front panels |
| Suitable for front panel width | 450 mm 17.7 " |
| Note | The support arm connection may be swapped over by rotating the enclosure 3 mm double-bit lock insert may be exchanged for 41 mm lock inserts, plastic handles and T handles, type C |
| OUT_SUITABLE_FOR_FRONT_PAN EL_HEIGHT | 350 mm 13.8 " |
| Packaging unit | 1 pc(s). |
| Net weight | 30.999 lb |
| Gross weight | 30.999 lb |

Features

Customs tariff number 9403200082

Approvals

Approvals UL + C-UL (listed)