

Rittal – The System.

Faster – better – everywhere.



WM 8017.596

WM wall-mounted disconnect enclosure

State: 4/22/2026 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



WM 8017.596 - WM wall-mounted disconnect enclosure

These flange mount disconnect wallmount enclosures can be used for virtually any application. The WM series ensures NEMA protection through a secure locking system, foamed-in-place gasket, and knife-edge sealing surface. Features include a cold rolled steel body and door, and a zinc plated mounting panel.



Features

| | |
|---------------------|--|
| Model No. | WM 8017.596 |
| Product description | These flange mount disconnect wallmount enclosures can be used for virtually any application. The WM series ensures NEMA protection through a secure locking system, foamed-in-place gasket, and knife-edge sealing surface. Features include a cold rolled steel body and door, and a zinc plated mounting panel. |
| Material | Door: Carbon steel, 2.0 mm, all-round foamed-in PU seal Housing: Carbon steel Mounting plate: Carbon steel, zinc-plated |
| Surface finish | Dipcoat-primed and powder-coated, textured paint |
| Color | RAL 7035 |
| Supply includes | Housing with door(s) Door hinged on left Mounting plate Rear wall mounting holes Flange door with universal disconnect cutout 3-point latching L-Handle |

Features

| | |
|--------------------------------------|--|
| Dimensions | Width: 975 mm Height: 1,200 mm Depth: 400 mm Width: 38.4 " Height: 47.2 " Depth: 15.7 " |
| Dimensions of mounting plate (W x H) | 840 mm x 1,155 mm 33.1 " x 45.5 " |
| Protection category NEMA | NEMA 4 UL Type 4/3R/12 |
| Material thickness - door | 2 mm 0.08 " |
| Material thickness - enclosure | 2 mm 0.08 " |
| Material thickness - mounting plate | 3 mm 0.12 " |
| Packaging unit | 1 pc(s). |
| Net weight | 211.64 lb |
| Gross weight | 212 lb |
| Customs tariff number | 8538100000 |

Approvals

| | |
|--------------|---------------------------|
| Approvals | UL + C-UL (listed) |
| Explanations | Declaration of conformity |
